




Datasheet

RLED20+CC4

4-Channel Constant Current Dimmer



What is the RLED20+CC4?

The RLED20+CC4 is a Wireless 4-channel constant current dimmer used in a Rako Wireless system.


Each channel on the RLED20+CC4 can be independently controlled to mix RGBW to create customised colour outputs.

The RLED20+CC4 has been designed for flexible installation, for a retrofit solution it can be installed behind a ceiling or if the lighting is wired back to a central location it can be mounted centrally using the supplied mounting bracket.

Features

- Manual test button
- Up to 16 Scenes
- Controllable from any Rako Wireless transmitter
- Colour wheel

Connections/Dimensions



Technical Data

Dimensions	172x46x40mm
Input Supply	48V DC
Weight	178g
Housing	UL94-V0
Connections	2-way terminal for DC supply 8-way screw terminal for load connections
Climate Range	Temperature +2C to +40C Humidity +5% to 95% non-condensing
Load Types	Constant current LED's 350-700mA
Minimum Load	3W
Maximum Load	20W/Channel, 45V Max Forward Voltage
Terminal Size	4.0mm ²
Standards	RoHS UKCA, CE EN 60669-2-5:2016
Communication	FM radio, 433.9MHz

Installation and Setup

For information on installing and setting up the RLED20+CC4, see the [RLED20+CC4 Manual](#).



Document Version 2.0.0

telephone +44 (0) 1634 226666 | www.rakocontrols.com