




Datasheet

RK-EOS

Wireless NFC Programmable Keypad



What is the RK-EOS?

The RK-EOS is a six-button Wireless keypad used in a Rako Wireless system.

Each button on the RK-EOS can be configured via Rasoft Pro to transmit commands to multiple Rooms, providing additional flexibility for switch locations that may require multiple Rooms, such as on staircases or open-plan areas.

The RK-EOS is the programmable section and the RP-EOS-XX-XX is the cover plate and mounting kit which forms the front buttons, therefore the RP-EOS-XX-XX must be used in conjunction with the RK-EOS.

Technical Data

Dimensions	RK-EOS: 50x50x12mm Cover plate: 88x88x3mm
Fixing	Flush mounting into standard UK single gang back box, minimum 12mm depth.
Weight	RK-EOS: 24g Cover plate and grid: 141g
Input Supply	1 x CR2032 3V lithium coin cell battery
Climate Range	Temperature +2C to +40C Humidity +5% to 90% non condensing
Standards	RoHS UKCA, CE EN 60669-2-5:2016
Communication	FM radio, 433.9MHz


Button Configurations & Finishes

RP-EOS-


Button
Layout

Plate
Finish

Lighting Control




RP-EOS-60-XX




RP-EOS-30-XX

Blind Control



RP-EOS-61-XX



RP-EOS-31-XX



Polished Brass
RP-EOS-XX-PB



Polished Chrome
RP-EOS-XX-PC



Matt Bronze
RP-EOS-XX-BM



Satin Chrome
RP-EOS-XX-SC



Antique Brass
RP-EOS-XX-AB





Matt White
RP-EOS-XX-WH



Matt Black
RP-EOS-XX-MB

Connections/Dimensions

BATTERY INPUT
CR2032



Installation and Setup

For information on installing and setting up the RK-EOS, see the [RK-EOS Manual](#).



Document Version 2.0.0

telephone +44 (0) 1634 226666 | www.rakocontrols.com