



Datasheet

RK-EOS (Portrait)

Wireless NFC Programmable Keypad

What is the RK-EOS?

The RK-EOS is a six-button Wireless keypad used in a Rako Wireless system which is housed within a portrait cover plate.

Each button on the RK-EOS can be configured via Rasoft Pro to transmit commands to multiple Rooms, providing additional flexibility for switch locations that may require multiple Rooms, such as on staircases or open-plan areas.

The RK-EOS is the programmable section and the RP-EOS-PO-XX-XX is the cover plate and mounting kit which forms the front buttons, therefore the RP-EOS-PO-XX-XX must be used in conjunction with the RK-EOS.


Technical Data

Dimensions	RK-EOS: 50x50x12mm Cover plate: 115x76x3mm Backbox: 53x74x12mm
Weight	RK-EOS: 24g Cover plate and grid: 141g
Input Supply	1 x CR2032 3V lithium coin cell battery
Climate Range	Temperature +2C to +40C Humidity +5% to 90% non condensing
Standards	RoHS UKCA, CE EN 60669-2-5:2016
Communication	FM radio, 433.9MHz

Button Configurations & Finishes




Lighting Control



RP-EOS-PO-60-XX RP-EOS-PO-30-XX


Blind Control



RP-EOS-PO-61-XX RP-EOS-PO-31-XX

- Polished Brass**
RP-EOS-PO-XX-PB
- Polished Chrome**
RP-EOS-PO-XX-PC
- Matt Bronze**
RP-EOS-PO-XX-BM
- Satin Chrome**
RP-EOS-XX-PO-SC
- Antique Brass**
RP-EOS-PO-XX-AB
- Matt White**
RP-EOS-PO-XX-WH
- Matt Black**
RP-EOS-PO-XX-MB

Dimensions



Installation and Setup

For information on installing and setting up the RK-EOS, see the [RK-EOS Manual](#).

